ARTHEMYA®

SOLID OAK 3D DECORATIVE ELEMENTS - CE Marking:

ARTHEMYA **18**	
SR EN 14342:2013 **SOLID OAK 3D DECORATIVE ELEMENTS** **QUERCUS SPP.** **(SR EN 13226:2009)**	
Reaction to fire	Dfl-s1/Cfl-s1
Density	600/800 kg/m^3
Thickness	11-13.2 mm
Formaldehyde emission	E1
Slip resistance	100 USRV
Thermal conductivity	0,165 W/mK, for d=675 kg/m^3
Thermal resistance	0,127m^2K/W, for th. = 0,021 m
Durability	Class 1/2-S-M
Finish	Unfinished

DOUBLE LAYER 3D DECORATIVE ELEMENTS - CE Marking:

ARTHEMYA **18**	
SR EN 14342:2013 **DOUBLE LAYER 3D DECORATIVE ELEMENTS** **OAK, QUERCUS SPP./BIRCH PLYWOOD** **(SR EN 13489:2003)**	
Reaction to fire	Dfl-s1/Cfl-s1
Density	500/700 kg/m^3
Thickness	11-13.2 mm
Formaldehyde emission	E1
Slip resistance	100 USRV
Thermal conductivity	0,145 W/mK, for d=575 kg/m^3
Thermal resistance	0,092 m^2K/W, for th. = 0,0134 m
Durability	Class 1 and 2
Finish	Unfinished